


WEY BUTTERFLY VALVES TF20 FREE SHAFT




Dimensions

9.3.10

DN 80 – 800




DN 900 - 1600



General dimensions															Top flange ISO 5211						
DN [mm]		A	B	C	ø D	E	F	ø G	K			L	M	Kg	ISO	ø Q	ø R	S	T	axb	
									PN10	PN16	ANSI cl. 150										
80	3"	141	110	10	200	30	11	90	160	160	152.4	46	65	5.3	F-07	70	4x9				
100	4"	165	115	10	230	30	11	90	180	180	190.5	52	90	7	F-07	70	4x9				
125	5"	180	127	12	255	33	14	90	210	210	215.9	56	112	9.5	F-07	70	4x9				
150	6"	193	143	12	285	33	14	90	240	240	241.3	56	139	11	F-07	70	4x9				
200	8"	225	173	12	345	33	17	90	295	295	298.5	60	191	18.4	F-07	70	4x9				
250	10"	283	210	14	406	30	22	130	350	355	361.9	68	241	30.8	F-10	102	4x12	3	70		
300	12"	308	240	14	480	30	22	130	400	410	431.8	78	290	45.3	F-10	102	4x12	3	70		
350	14"	339	271	14	535	31	22	160	460	470	476.2	78	338	55	F-10	102	4x12	3	70		
400	16"	380	308	18	597	31	27	160	515	525	539.7	102	387	80	F-12	125	4x14	4	85		
450	18"	381	340	20	640	38	36	190	565	585	577.8	114	434	99.9	F-14	140	4x18	4	100		
500	20"	433	380	22	700	38	36	210	620	650	635	127	478	137	F-14	140	4x18	4	100		
600	24"	494	440	24	834	48	46	210	725	770	749.3	154	570	220	F-16	165	4x22	5	130		
700	28"	560	485	25	927	73	46	300	840	840	863.5	165	660	282	F-25	254	8x18	5	200		
750	30"	590	530	25	995	82	55	300	900	900	914.4	190	705	350	F-25	254	8x18	5	200		
800	32"	630	565	29	1060	82	55	300	950	950	978	190	763	398	F-25	254	8x18	5	200		
900	36"	695	610	32	1170	110	72	350	1050	1050	1086	203	866	511	F-25	254	8x18	5	200	20x12	
1000	40"	770	675	32	1290	110	72	350	1160	1170	1200	216	966	686	F-25	254	8x18	5	200	20x12	
1100	44"	815	733	32	1405	110	72	350	1270	1270	1314.5	216	1054	865	F-25	254	8x18	5	200	20x12	
1200	48"	875	818	40	1485	110	98	350	1380	1390	1422	254	1153	1072	F-30	298	8x23	5	230	28x16	
1400	56"	1000	969	35	1735	120	98	415	1590	1590	1651	280	1342	1584	F-30	298	8x23	5	230	28x16	
1500	60"	1075	1050	40	1855	160	130	475	1700	1710	1759	318	1447	2110	F-40	406	8x39	8	300	32x18	
1600	64"	1115	1090	40	1930	160	130	475	1820	1820		318	1533	2153	F-40	406	8x39	8	300	32x18	

TF20 flanged U-type



Variant screws

Variant threaded bolts

Additional 4 screws on both sides
for the centring holes at DN 450
and DN 700-1600

DN [mm]		E	PN10							PN16							ANSI cl. 150						
			K	e	M	L	L1	N°	K	e	M	L	L1	N°	K	e	M	L	L1	N°			
80	3"	46	160	20	M16	110	130	8	160	20	M16	110	130	8	152.4	23.8	5/8"	M16	110	130	4		
100	4"	52	180	20	M16	110	130	8	180	20	M16	110	130	8	190.5	23.8	5/8"	M16	120	140	8		
125	5"	56	210	22	M16	120	140	8	210	22	M16	120	140	8	215.9	23.8	3/4"	M20	130	150	8		
150	6"	56	240	22	M20	130	150	8	240	22	M20	130	150	8	241.3	25.4	3/4"	M20	130	150	8		
200	8"	60	295	24	M20	130	160	8	295	24	M20	130	160	12	298.5	28.6	3/4"	M20	140	160	8		
250	10"	68	350	26	M20	150	170	12	355	26	M24	150	170	12	361.9	30.2	7/8"	M24	160	180	12		
300	12"	78	400	26	M20	160	180	12	410	28	M24	160	180	12	431.8	31.7	7/8"	M24	170	190	12		
350	14"	78	460	26	M20	170	180	16	470	30	M24	170	190	16	476.2	34.9	1"	M27	180	200	12		
400	16"	102	515	26	M24	180	210	16	525	32	M27	200	220	16	539.7	36.5	1"	M27	210	230	16		
450	18"	114	565	26	M24	190	220	16	585	32	M27	210	240	16	577.8	39.7	1.1/8"	M30	230	250	16		
					M24	60	8	M27			60	8											
500	20"	127	620	28	M24	210	230	20	650	34	M30	230	260	20	635	46	1.1/8"	M30	250	280	20		
600	24"	154	725	28	M27	240	270	20	770	36	M33	260	290	20	749.3	47.6	1.1/4"	M33	280	310	20		
700	28"	165	840	30	M27	260	280	20	840	36	M33	270	300	20	863.5	52.5	1.1/4"	M33	310	340	24		
					M27	80	8	M33			85	8											
750	30"	190	900	32	M30	290	320	20	900	38	M33	300	340	20	914.4	54	1.1/4"	M33	335	375	24		
					M30	95	8	M33			100	8											
800	32"	190	950	32	M30	290	320	20	950	38	M36	310	345	20	978	57	1.1/2"	M39	340	380	24		
					M30	110	8	M36			80	8											
900	36"	203	1050	34	M30	310	350	24	1050	40	M36	330	375	24	1086	60	1.1/2"	M39	370	415	28		
					M30	100	8	M36			100	8											
1000	40"	216	1160	34	M33	325	360	24	1170	42	M39	345	390	24	1200	63.5	1.1/2"	M39	390	430	32		
					M33	95	8	M39			100	8											
1100	44"	216	1270	38	M33	330	370	28	1270	48	M39	360	400	28	1314.5	101	1.1/2"	M39	465	510	36		
					M33	100	8	M39			100	8											
1200	48"	254	1380	38	M36	375	420	28	1390	48	M45	395	445	28	1422	108	1.1/2"	M39	475	520	40		
					M36	110	8	M45			115	8											
1400	56"	280	1590	42	M39	410	450	32	1590	52	M45	440	490	32	1651	124	1.3/4"	M45	580	630	44		
					M39	100	8	M45			110	8											
1500	60"	318	1700	48	M39	460	505	32	1710	54	M52	490	550	32	1759	132	1.3/4"	M45	635	690	44		
					M39	110	8	M52			110	8											
1600	64"	318	1820	56	M45	460	510	36	1820	58	M52	490	550	36									
					M45	110	8	M52			120	8											

For butterfly valves designed specifically for ANSI class 150 connection, the threads of the centring holes are machined to UNC (inch threads, dimension «M»).